



Robot QRC 320 mechanics

The robot mechanics QRH320/350/410 is a six-axis articulated arm robot. The robot is usually positioned upright or overhead. The QRC320/350/410 is mounted on a base or directly at a robot positioner. The QRC robot has a standard wrist where welding torches, flame cutters and other working tools with a weight of up to 15/10 kg can be mounted. The integration of a changing tool on the wrist allows to use more processes with a robot. Applications:- MIG/MAG Welding

- Plasma and oxygen cutting
- Plasma and Plasma powder welding
- Stud welding
- Easy handling tasks

Technical Data

Swivelling range axis 1	+170° / -170°
Swivelling range axis 2	+125° / -90°
Swivelling range axis 3	+80 / -210°
Swivelling range axis 4	+179° / -179°
Swivelling range axis 5	+135° / -135°
Swivelling range axis 6	+300° / -300°
Swivelling speed axis 1	184
Swivelling speed axis 2	184
Swivelling speed axis 3	177
Swivelling speed axis 4	497
Swivelling speed axis 5	542
Swivelling speed axis 6	528
Operating range	Ø 4200 mm
Operating range Axis 5 +90°	Ø 3200 mm
Operating range height	2470
Pay load	15,00
Repeatability	s +/- 0,1 mm
Collision radius	500
Floor space	Ø 500 mm
Weight	235

Features

Technical features

- Less wear and improved, more user-friendly operation via optimised cables, plugs and motor protection
- Higher dynamics and weight reduction due to a leaner product design with rounded ergonomic forms
- Highest flexibility in the equipment by modular design of the robot mechanics
- Best processing quality due to a high repeatability
- High offset speeds reduce the cycle times
- Digital AC drives
- For floor or overhead mounting
- Absolute path measuring system

Options

Available options

- Colour freely selectable
- Calibrated mechanics
- Accessories